

# SPECIFICATION

# Aluminium Deck Support System

PRODUCT	DESCRIPTION	DIMENSIONS	PRODUCT CODE	MATERIAL	QTY
 <p>Aluminium substructure joist (DS38)</p>	<p>Aluminium joists with continuous fixing channel.</p>	<p>Width: 48mm Depth: 38mm Length: 3600mm</p>	<p>gRYAJ38</p>	<p>Aluminium Alloy 6063 / powder coated to RAL 9005</p>	<p>Each</p>
 <p>Aluminium corner connector 90°</p>	<p>Connects two joists to create a 90° angle.</p>	<p>n/a</p>	<p>gRYACC</p>	<p>Aluminium Alloy 6063</p>	<p>Each</p>
 <p>Aluminium adjustable corner connector 135°</p>	<p>Connects two joists to create a 135° angle.</p>	<p>n/a</p>	<p>gRYAACC</p>	<p>Aluminium Alloy 6063</p>	<p>Each</p>
 <p>Aluminium straight connector</p>	<p>Connects two joists end-to-end.</p>	<p>n/a</p>	<p>gRYASC</p>	<p>Aluminium Alloy 6063</p>	<p>Each</p>
 <p>Self-levelling pedestals – various heights</p>	<p>Allows the deck to overcome different surface levels to create a flat deck. Also ideal for concealing services, ductwork and pipes beneath the deck.</p> <p>Special 'clip-on' head (pictured) for use with aluminium bearers.</p> <p>Standard decking head for use with timber bearers. Ask for more information.</p>	<p>Base diameter: 210-220mm Head diameter: 135mm Bearer width capacity: 20-100mm</p> <p>Various heights available: 40-56mm, 50-70mm, 70-110mm, 110-160mm, 150-210mm, 200-300mm, Larger sizes available on request</p>	<p>gRYPED40 gRYPED50 gRYPED70 gRYPED110 gRYPED150 gRYPED200 On request</p>	<p>Recyclable, UV resistant polypropylene. Resistant to mould, algae, alkali and bitumen</p>	<p>Box of 25</p>
 <p>Adjustable cradle</p>	<p>Ideal when the decking needs to be elevated off the ground by a minimal height. Ideal for patios and balconies. For use with timber or aluminium joists.</p>	<p>Base diameter: 90mm. Bearer width capacity: 44-48mm Height range: 10-40mm</p>	<p>gRYACR</p>	<p>Recycled glass filled Nylon. Resistant to moulds, algae, alkali and bitumen</p>	<p>Box of 50</p>
 <p>Stainless steel joist screw</p>	<p>Stainless steel pan head self-drill screw with square drive. Must be used with the connectors to secure joists.</p>		<p>gRYJS</p>	<p>Stainless steel</p>	<p>Bag of 200</p>
 <p>Stainless steel self-drill for Trex Universal Clips</p>	<p>Stainless steel CSK head self-drill pilot-point screw. Must be used when installing Trex decking onto the aluminium deck support system.</p>		<p>gRYDS</p>	<p>Stainless steel with matt black finish</p>	<p>Bag of 200</p>