



Trex® Protect™
JOIST, BEAM & RIM TAPE



Trex® Protect™
JOIST, BEAM & RIM TAPE

To calculate what you need, visit our materials estimator at:
trexprotect.com/materials-estimator



Visit trexprotect.com
or call 1-877-348-1385

EXTEND THE LIFE
of your deck

*Protect your
deck from
moisture with*

TREX® PROTECT®

JOIST, BEAM & RIM TAPE

20
YEAR
WARRANTY



HOW IT WORKS

Trex Protect Joist, Beam and Rim Tape is a self-adhesive butyl tape designed to protect the top of joists and beams from moisture that can lead to wood rot and decay.

BENEFITS

- » Protects all horizontal and vertical surfaces including joists, rim joists, beams, steps, stair stringers, blocking, ledger board and other surfaces
- » Helps deck screws hold longer and stronger
- » Acts as a barrier between wood and galvanized metal such as joist hangers
- » Eliminates splitting from freeze and thaw
- » Provides a non-skid surface for safe installation
- » Provides a waterproof barrier under the fascia board

INSTALLATION

Trex Protect Joist, Beam and Rim Tape can be applied to horizontal and vertical surfaces.

Trex Protect tape has three widths making it convenient to apply to joists, double beams, rims, and all flat wood surfaces.

- » Use 1-5/8" x 50' (4.13 cm x 15.24 m) Joist Tape for joists
- » Use 3-1/8" x 50' (7.94 cm x 15.24 m) Beam Tape for all double beams
- » Use 11" x 50' (27.94 cm x 15.24 m) Rim Tape for rim joists, stairs and all flat-blocked surfaces

1

CLEAN THE WOOD SURFACE
MAKING SURE IT IS DRY
AND FREE OF ANY DEBRIS



2

REMOVE THE BUTYL TAPE BACKING WHILE
APPLYING DIRECTLY TO THE SURFACE. RUN
YOUR HAND OVER THE TAPE AND FIRMLY
PRESS IT ON TO THE WOOD SURFACE.



3

AFTER COVERING ALL HORIZONTAL
AND VERTICAL SURFACES, CUT THE
TAPE TO LENGTH WITH A UTILITY
KNIFE OR SCISSORS

